

**IMPORTANT** - READ CAREFULLY BEFORE INSTALLING FIXTURE. RETAIN THESE INSTRUCTIONS FOR FUTURE REFERENCE.  
 THIS PRODUCT MUST BE INSTALLED IN ACCORDANCE WITH THE NATIONAL ELECTRICAL CODE AND ALL APPLICABLE LOCAL CODES, BY A PERSON FAMILIAR WITH THE CONSTRUCTION AND OPERATION OF THE PRODUCT, AND THE HAZARDS INVOLVED. PROPER GROUNDING IS REQUIRED FOR SAFETY.

**INSTALLATION WITH 4" JUNCTION BOX  
 INTEGRAL DRIVER (120-277V)  
 DIMMING 0-10V OR TRIAC / ELV (LTV) (120V ONLY)**

- A- MAKE ALL NECESSARY ELECTRICAL CONNECTIONS INTO THE JUNCTION BOX.
- B- INSTALL THE CROSSBAR, GASKET AND MOUNTING PLATE USING PROVIDED SCREWS.
- C- UNFASTEN THE FIXTURE'S SET SCREWS (3X) USING ALLEN KEY PROVIDED IN ORDER TO RELEASE THE FIXTURE MOUNTING BASE.
- D- INSTALL FIXTURE MOUNTING BASE USING PROVIDED SCREWS WITH RUBBER WASHERS (2X).
- E- INSTALL FIXTURE AND FASTEN THE SET SCREWS (3X).

A - E

**WIRING DIAGRAM**

LIVE	BLACK
NEUTRAL	WHITE
	GREEN
DIM +	PURPLE or RED
DIM -	GRAY or BLUE

